

Multi PCSK

Modularity.

Easy maintenance.


Up to 4 independent DC inputs.

Advanced grid support.

Compatible with all battery technologies.



Freemaq Multi PCSK




690 V		FRAME 2	FRAME 3	FRAME 4	
REFERENCES		FP2195K2	FP3290K3	FP4390K2	FP4390K4
AC	AC Output Power (kVA/kW) @40 °C ^[1]	2195	3290	4390	
	AC Output Power (kVA/kW) @50 °C ^[1]	2035	3055	4075	
	Operating Grid Voltage (VAC)	690 V ±10%			
DC	DC Voltage Range ^[2]	976 V - 1500 V			
	Maximum DC Voltage	1500 V			
	Number of Separate DC Inputs	2	3	2	4
EFFICIENCY	Efficiency (Max) (η)	98.84%	98.87%	98.94%	
	Euroeta (η)	98.34%	98.49%	98.51%	
660 V		FRAME 2	FRAME 3	FRAME 4	
REFERENCES		FP2101K2	FP3151K3	FP4200K2	FP4200K4
AC	AC Output Power (kVA/kW) @40 °C ^[1]	2100	3150	4200	
	AC Output Power (kVA/kW) @50 °C ^[1]	1950	2925	3900	
	Operating Grid Voltage (VAC)	660 V ±10%			
DC	DC Voltage Range ^[2]	934 V - 1500 V			
	Maximum DC Voltage	1500 V			
	Number of Separate DC Inputs	2	3	2	4
EFFICIENCY	Efficiency (Max) (η)	98.86%	98.89%	98.95%	
	Euroeta (η)	98.36%	98.51%	98.53%	
645 V		FRAME 2	FRAME 3	FRAME 4	
REFERENCES		FP2055K2	FP3080K3	FP4105K2	FP4105K4
AC	AC Output Power (kVA/kW) @40 °C ^[1]	2055	3080	4105	
	AC Output Power (kVA/kW) @50 °C ^[1]	1905	2855	3810	
	Operating Grid Voltage (VAC)	645 V ±10%			
DC	DC Voltage Range ^[2]	913 V - 1500 V			
	Maximum DC Voltage	1500 V			
	Number of Separate DC Inputs	2	3	2	4
EFFICIENCY	Efficiency (Max) (η)	98.85%	98.88%	98.81%	
	Euroeta (η)	98.24%	98.39%	98.41%	
630 V		FRAME 2	FRAME 3	FRAME 4	
REFERENCES		FP2005K2	FP3005K3	FP4010K2	FP4010K4
AC	AC Output Power (kVA/kW) @40 °C ^[1]	2005	3005	4010	
	AC Output Power (kVA/kW) @50 °C ^[1]	1860	2790	3720	
	Operating Grid Voltage (VAC)	630 V ±10%			
DC	DC Voltage Range ^[2]	891 V - 1500 V			
	Maximum DC Voltage	1500 V			
	Number of Separate DC Inputs	2	3	2	4
EFFICIENCY	Efficiency (Max) (η)	98.79%	98.82%	98.88%	
	Euroeta (η)	98.28%	98.43%	98.45%	
615 V		FRAME 2	FRAME 3	FRAME 4	
REFERENCES		FP1955K2	FP2935K3	FP3915K2	FP3915K4
AC	AC Output Power (kVA/kW) @40 °C ^[1]	1955	2935	3915	
	AC Output Power (kVA/kW) @50 °C ^[1]	1815	2725	3635	
	Operating Grid Voltage (VAC)	615 V ±10%			
DC	DC Voltage Range ^[2]	870 V - 1500 V			
	Maximum DC Voltage	1500 V			
	Number of Separate DC Inputs	2	3	2	4
EFFICIENCY	Efficiency (Max) (η)	98.75%	98.78%	98.77%	
	Euroeta (η)	98.20%	98.35%	98.37%	

NOTES

[1] Values at 1.00-Vac nom and CosPhi=1. The maximum AC output power must be limited to meet the P-Q capability requirement at the inverter level of some grid codes. Consult Power Electronics for derating curves.

[2] Consult Power Electronics for derating curves. In the event of overvoltage in the grid, the minimum DC voltage will vary proportionally with the AC voltage.

Freemaq Multi PCSK




600 V		FRAME 2	FRAME 3	FRAME 4	
REFERENCES		FP1910K2	FP2865K3	FP3820K2	FP3820K4
AC	AC Output Power (kVA/kW) @40 °C ^[1]	1910	2865	3820	
	AC Output Power (kVA/kW) @50 °C ^[1]	1775	2660	3545	
	Operating Grid Voltage (VAC)	600 V ±10%			
DC	DC Voltage Range ^[2]	849 V - 1500 V			
	Maximum DC Voltage	1500 V			
	Number of Separate DC Inputs	2	3	2	4
EFFICIENCY	Efficiency (Max) (η)	98.82%	98.85%	98.78%	
	Euroeta (η)	98.18%	98.33%	98.35%	
530 V		FRAME 2	FRAME 3	FRAME 4	
REFERENCES		FP1685K2	FP2530K3	FP3370K2	FP3370K4
AC	AC Output Power (kVA/kW) @40 °C ^[1]	1685	2530	3370	
	AC Output Power (kVA/kW) @50 °C ^[1]	1565	2350	3130	
	Operating Grid Voltage (VAC)	530 V ±10%			
DC	DC Voltage Range ^[2]	750 V - 1500 V			
	Maximum DC Voltage	1500 V			
	Number of Separate DC Inputs	2	3	2	4
EFFICIENCY	Efficiency (Max) (η) (preliminary)	98.78%			
	Euroeta (η) (preliminary)	98.35%			
500 V		FRAME 2	FRAME 3	FRAME 4	
REFERENCES		FP1590K2	FP2385K3	FP3180K2	FP3180K4
AC	AC Output Power (kVA/kW) @40 °C ^[1]	1590	2385	3180	
	AC Output Power (kVA/kW) @50 °C ^[1]	1475	2215	2955	
	Operating Grid Voltage (VAC)	500 V ±10%			
DC	DC Voltage Range ^[2]	708 V - 1500 V			
	Maximum DC Voltage	1500 V			
	Number of Separate DC Inputs	2	3	2	4
EFFICIENCY	Efficiency (Max) (η) (preliminary)	98.78%			
	Euroeta (η) (preliminary)	98.35%			
480 V		FRAME 2	FRAME 3	FRAME 4	
REFERENCES		FP1525K2	FP2290K3	FP3055K2	FP3055K4
AC	AC Output Power (kVA/kW) @40 °C ^[1]	1525	2290	3055	
	AC Output Power (kVA/kW) @50 °C ^[1]	1415	2125	2840	
	Operating Grid Voltage (VAC)	480 V ±10%			
DC	DC Voltage Range ^[2]	679 V - 1500 V			
	Maximum DC Voltage	1500 V			
	Number of Separate DC Inputs	2	3	2	4
EFFICIENCY	Efficiency (Max) (η) (preliminary)	98.78%			
	Euroeta (η) (preliminary)	98.35%			

NOTES

[1] Values at 1.00-Vac nom and CosPhi=1. The maximum AC output power must be limited to meet the P-Q capability requirement at the inverter level of some grid codes. Consult Power Electronics for derating curves.

[2] Consult Power Electronics for derating curves. In the event of overvoltage in the grid, the minimum DC voltage will vary proportionally with the AC voltage.

Freemaq Multi PCSK



COMMON FEATURES		FRAME 2	FRAME 3	FRAME 4	
AC	Max. AC Output Current (A) @40 °C	1837	2756	3674	
	Operating Grid Frequency (Hz)	50/60 Hz			
	Current Harmonic Distortion (THDi)	<3% per IEEE519			
	Power Factor (CosPhi) ^[1]	0.5 leading... 0.5 lagging			
	Reactive Power Compensation	Four quadrant operation			
	Overload Capability ^[5]	166% - 100 ms / 150% - 5 s / 120% - 8 s / 110% - 15 s			
DC	DC Voltage Ripple	<3%			
	Max. DC Continuous Current per Input (A)	1148	1148	2295	1148
	Max. DC Short Circuit Current per Input (kA)	500 kA with a time constant of 1 ms			
	Battery Technology	All type of batteries (BMS required)			
	Number of Separate DC Inputs	2	3	2	4
CABINET	Dimensions [WxDxH] (ft)	9.8 x 6.5 x 7.5			
	Dimensions [WxDxH] (m)	3.0 x 2.0 x 2.3			
	Weight (lbs)	8600	9700	10365	
	Weight (kg)	3900	4400	4700	
	Type of Ventilation	Forced air cooling			
ENVIRONMENT	Degree of Protection	NEMA 3R / IP55			
	Operating Temperature Range ^[2]	From -40 °C to +60 °C, >40 °C power derating			
	Operating Relative Humidity Range	From 4% to 100%			
	Storage Temperature Range	From -40 °C to +60 °C			
	Max. Altitude (above sea level)	2000m / >2000m power derating (Max. 4000m)			
CONTROL	Communication Protocol	Modbus TCP			
	Power Plant Controller	Optional. Third party SCADA systems supported			
	Keyed ON/OFF Switch	Standard			
PROTECTIONS	Ground Fault Protection	Insulation monitoring device			
	Humidity Control	Active heating			
	General AC Protection & Disconn.	Circuit breaker			
	General DC Protection & Disconn. ^[3]	High-speed fuses, Motorized DC disconnect switches			
	Overvoltage Protection	Type II for AC and Type I+II for DC			
STANDARDS	Safety	UL 1741 / CSA 22.2 No.1071-16 / IEC 62109-1 / IEC 62109-2 / IEC 62477-1			
	Installation	NEC 2023			
	Utility Interconnect ^[4]	IEEE 1547:2018 / UL 1741 SA & SB/ IEC 62116:2014			

NOTES

[1] Consult P-Q charts available: $Q(kVA) = \sqrt{(S(kVA))^2 - P(kW)^2}$.

[2] Optional available for temperatures below -25 °C.

[3] Battery short circuit disconnection has to be done on the battery side.

[4] Consult Power Electronics for other applicable standards/grid codes.

[5] Available from January 2027.