
Multi PCSM

UL

Easy maintenance.
Integrated MV solution in the same enclosure.
Up to 4 independent DC inputs.
Advanced grid support.
Compatible with all battery technologies.



Freemaq Multi PCSM
UL



REFERENCES		FP4997U2	FP4997U4	FP5020MU2	FP5020MU4
AC	AC Output Power @30 °C [1]	5240 kVA / 4999 kW		5240 kVA / kW	
	AC Output Power @35 °C [1]	5020 kVA / 4999 kW		5020 kVA / kW	
	AC Output Power @40 °C [1]	4800 kVA / kW			
	AC Output Power @50 °C [1]	4360 kVA / kW			
	Operating Grid Voltage	34.5 kV ±10%			
	Rated Impulse Withstand Voltage	150 kV			
	Operating Grid Frequency	60 Hz			
	Current Harmonic Distortion (THDi)	<3% per IEEE 519			
	Power Factor (CosPhi) [2]	0.5 leading ... 0.5 lagging			
	Reactive Power Compensation	Four quadrant operation			
	Overload Capability	166% - 100 ms / 150% - 5 s / 120% - 8 s / 110% - 15 s			
DC	DC Voltage Range [3]	976 V – 1500 V			
	Maximum DC Voltage	1500 V			
	DC Voltage Ripple	<3%			
	Max. DC Continuous Current	2613 A	1310 A	2740 A	1370 A
	Max. DC Short Circuit Current per Input	500 kA with a time constant of 1 ms			
	Battery Technology	All type of batteries (BMS required)			
	Number of Separated DC Inputs	2	4	2	4
EFFICIENCY & AUX. SUPPLY	Efficiency (Max) (η)	98.02% including MV transformer			
	CEC (η)	97.75% including MV transformer			
CABINET	Footprint dimensions [WxDxH]	21.3 x 6.5 x 7.5 ft			
	Footprint dimensions [WxDxH]	6.5 x 2.0 x 2.3 m			
	Weight	30865 lbs			
	Weight	14000 kg			
	Type of Ventilation	Forced air cooling			
ENVIRONMENT	Degree of Protection	NEMA 3R			
	Operating Temperature Range	From -40 °C to +60 °C, >30 °C power derating (optional below -25 °C)			
	Operating Relative Humidity Range	From 4% to 100%			
	Storage Temperature Range	From -40 °C to +60 °C			
	Max. Altitude (above sea level) [4]	2000 m			
CONTROL	Communication Protocol	Modbus TCP			
	Grid Forming (VISMA) / Black Start Capable	Standard			
PROTECTIONS	Ground Fault Protection	Insulation monitoring device			
	Humidity Control	Active heating			
	General AC Protection & Disconnection	38 kV MV switchgear (V)			
	General DC Protection & Disconnection	High-speed fuses, Motorized DC disconnect switches [5]			
	Overvoltage Protection	Type II for AC and Type I+II for DC			
STANDARDS	Safety	UL 1741 / CSA 22.2 No.107.1-16			
	Installation	NEC 2023			
	Utility Interconnect [6]	UL 1741 SA & SB / IEEE 1547.1 / IEEE 2800			

NOTES

[1] Values at 1.00·Vac nom and CosPhi=1. Consult Power Electronics for derating curves.
[2] Consult P-Q charts available: $Q(kVAr)=\sqrt{(S(kVA)^2-P(kW)^2)}$.
[3] Consult Power Electronics for derating curves. In the event of overvoltage in the grid, the minimum DC voltage will vary proportionally with the AC voltage.
[4] Consult Power Electronics for altitudes above 1000 m.
[5] Battery short circuit disconnection must be done on the battery side.
[6] Consult Power Electronics for other applicable standards / grid codes.

The content of this document is periodically updated. Power Electronics reserves the right to modify all or part of this document without prior notice.

V. 2.0.4 20261027

POWER ELECTRONICS