


NB City

UL

Multiple connection options
Dynamic power control
Customizable design





Model	BASIC	ADVANCED	PROFESSIONAL
AC input [V]	208 (L1, L2, PE) / 240 (L1, L2, PE) / 277 (L1, N, PE)		
Maximum output power per connector [kW]	6.7 / 7.7		
Energy measurement	Internal energy measurement		
	-	-	Revenue meter ^[1]
Communications	Wifi		
	-	-	3G/4G connectivity
	Ethernet		
	OCPP 1.6		
Authentication	RFID card reader		
Protections	-	CCID	CCID
	-	MCB	MCB
	-	Surge arrester Type 2 ^[1]	Surge arrester Type 2 ^[1]
External enclosure	NEMA 3R		
	White colour (RAL 9016 - microtexture painting)		
	C4 anti-corrosion protection ^[2]		
Glass colour	Black		
Operating temperature	From -13°F to 122°F		
Relative humidity	4% - 95%		
Interface	Status indicator		
Dimensions (W x D x H) [ft]	1.15 x 0.65 x 4.27		
Regulation	UL 2594, FCC Part 15 Class B, NEC 625		

	FRAME AC INPUT [V]	MODEL	REFERENCE	TYPE OF CONNECTOR
STANDARD MODELS	208 / 240 (L1, L2, PE)	BASIC	NBCUB28	2 x AC Type 2 (Plug - 13.1 ft spiral)
		ADVANCED	NBCUA28	2 x AC Type 2 (Plug - 13.1 ft spiral)
		PROFESSIONAL	NBCUP28	2 x AC Type 2 (Plug - 13.1 ft spiral)
	277 (L1, N, PE)	PROFESSIONAL	NBCUP38	2 x AC Type 2 (Plug - 13.1 ft spiral)

AVAILABLE OPTIONS	Cable lenght Normally is 13.1 ft of spiral, but you could also have 18 ft of straight cable	Dynamic power control One option < 300 A
-------------------	---	--

NOTES

- [1] Not included in models at 277 V (input voltage).
 [2] C3 anti-corrosion protection for stainless steel enclosure.