


Multi PCSK

Modularity.
Easy maintenance.
Up to 4 independent DC inputs.
Advanced grid support.
Compatible with all battery technologies.





		720 V	
REFERENCES	FP5150K2	FP5150K4	
AC	AC Output Power (kVA/kW) @30 °C ^[1]	5360	
	AC Output Power (kVA/kW) @35 °C ^[1]	5150	
	AC Output Power (kVA/kW) @40 °C ^[1]	4940	
	AC Output Power (kVA/kW) @50 °C ^[1]	4520	
	Max. AC Output Current (A) @30 °C	4298	
	Operating Grid Voltage (V)	720 V ±10%	
	Operating Grid Frequency (Hz)	50 / 60 Hz	
	Current Harmonic Distortion (THDi)	<3% per IEEE 519	
	Power Factor (CosPhi) ^[2]	0.5 leading... 0.5 lagging	
	Reactive Power Compensation	Four quadrant operation	
	Overload Capability	166% - 100 ms / 150% - 5 s / 120% - 8 s / 110% - 15 s	
DC	DC Voltage Range Full Power ^[3]	1019 V - 1500 V	
	Maximum DC Voltage	1500 V	
	DC Voltage Ripple	<3%	
	Max. DC Continuous Current (A)	2684	1342
	Max. DC Short Circuit Current per Input (kA)	500 kA with a time constant of 1 ms	
	Battery Technology	All type of batteries (BMS required)	
EFFICIENCY & AUX. SUPPLY	Efficiency (Max) (η)	98.94%	
	CEC (η)	98.51%	
CABINET	Dimensions [WxDxH] (ft)	9.8 x 6.5 x 7.5	
	Dimensions [WxDxH] (m)	3.0 x 2.0 x 2.3	
	Weight (lbs)	10365	
	Weight (kg)	4700	
	Type of Ventilation	Forced air cooling	
ENVIRONMENT	Degree of Protection	NEMA 3R / IP55	
	Operating Temperature Range ^[4]	From -40 °C to +60 °C, >30 °C power derating	
	Operating Relative Humidity Range	From 4% to 100%	
	Storage Temperature Range	From -40 °C to +60 °C	
	Max. Altitude (above sea level)	2000 m / >2000 m power derating (max. 4000 m)	
CONTROL	Communication Protocol	Modbus TCP	
	Grid Forming (VISMA) / Black Start Capable	Standard	
PROTECTIONS	Ground Fault Protection	Insulation monitoring device	
	Humidity Control	Active heating	
	General AC Protection & Disconnection	Circuit breaker	
	General DC Protection & Disconnection	High-speed fuses, Motorized DC disconnect switches ^[5]	
	Overvoltage Protection	Type 2 for AC and Type 1+2 for DC	
	Safety	UL 1741 / CSA 22.2 No.107.1-16 / IEC 62109-1 / IEC 62109-2 / IEC 62477-1	
STANDARDS	Installation	NEC 2023	
	Utility Interconnect ^[6]	UL 1741 SA & SB / IEEE 1547.1 / IEC 62116 / G99 / VDE 4110-4120-4130 / CEI 0-16 / NTS 2.1 / EN 50549	

NOTES

- [1] Values at 1.00-Vac nom and CosPhi=1. Consult Power Electronics for derating curves.
[2] Consult P-Q charts available: $Q(kVar) = \sqrt{(S(kVA))^2 - P(kW)^2}$.
[3] Consult Power Electronics for derating curves. In the event of overvoltage in the grid, the minimum DC voltage will vary proportionally with the AC voltage.
[4] Optional available for temperatures below -25 °C.
[5] Battery short circuit disconnection must be done on the battery side.
[6] Consult Power Electronics for other applicable standards / grid codes.